



A variable rate control and monitoring system for seed drills

The RDS **Artemis** removes the need for a mechanically driven land wheel by operating the metering unit with an electric motor maintaining its speed proportional to forward speed.

Suitable for both seed or seed and fertilizer, the RDS **Artemis** is for fitting onto drills with an Accord-type pneumatic metering system.

Upgrading your seed drill with technology found on higher value machines maximises field efficiency and prolongs drill working life, deferring capital expenditure.

The system comprises an electric motor with sufficient power and torque for most types of conventional pneumatic metering units. A radar forward speed sensor provides a signal to the Motor Control Module, which controls the motor speed proportional to forward speed.

FEATURES & ADVANTAGES

Pre-start facility – to prime the seed mechanism before drilling, simply press the Pre-Start Button, wait a few seconds and pull away.

Simple & fast operator product calibration – press Drill Priming Button, dispense product into a container, weigh and enter information into the instrument.

Calibration ‘on the move’ - when application rates require changing, utilise the manual adjustment buttons.

Integrated SD card reader – allows basic data logging to produce field records. Prints in text or .csv format for uploading directly into a spreadsheet or yield map proprietary software packages.

Precision Farming capability – add an RDS GPS 16 receiver and load a pre-defined seeding plan via SD card for automated variable seed rate application.

Printer option – useful for contractors to produce field records. Artemis also provides all the essential seed drill control and monitoring functions including:

- Forward speed
- Tramline count & control (symmetric & asymmetric)
- Two area totals (partial and total)
- Fan speed
- Hopper level alarms

TECHNICAL DETAILS	
Operating voltage:	11 - 28 Vdc
Keypad:	Rubber membrane - sealed
Display:	160 x 128 pixel (95 x 75mm)
Temperature range:	-30°C to +75°C operating -40°C to +85°C storage
Warranty:	2 years
Env. protection:	Instrument unit IP34 Full RFI/EMI protection
Dimensions:	220mm x 156mm x 52mm (W x H x D)

SYSTEM ENHANCEMENTS
RDS GPS 16 - GPS speed signal input for accurate forward speed measurement.
ICP 300 – in-cab printer for hard copy prints of field records

ALSO IN THE RANGE
Delta 34i Spreader Control - For variable rate fertiliser spreading.
Ceres 8000i – yield monitor and recording system for all types of combine harvester.

DISTRIBUTORS

RDS Technology Ltd, Cirencester Road,
Minchinhampton, Stroud, Glos GL6 9BH, UK
T: +44 (0)1453 733300 info@rdstec.com

www.rdstec.com

RDS TECHNOLOGY
— TOPCON POSITIONING GROUP —